sensoryco.

31145 Plantation Drive
Thousand Palms, California 92276
+1 760-385-3939
www.sensoryco.com

# SPRAYMOTION MACRO

## FX Systems for 4D & Simulator Environments






*Spraymotion Macro spray port assembly*

## Description

Our Spraymotion Macro system allows sequencing of water effects (i.e. mists, sprays, spritzers) to outside controls, adding a capability of triggering in three independent zones. Perfect for spray or spritzer effects that are delivered in a “macro” environment where effects come from overhead, Spraymotion Macro Spray Ports can be grouped in a variety of configurations up to a maximum of 25 total spray ports.

The Spraymotion effects are triggered by outside controls using relay contact closures in the Spraymotion Controller. Timing of the sprays can be dictated by outside controls or set manually in the Spraymotion Controller for each zone.

The Spraymotion system is designed to allow for easy implementation so that spray and spritzer effects can be successfully installed by any integrator or designer.

Spraymotion Macro effects can scale to very large indoor or outdoor settings.

## Specifications

| Parameter | Value |
|---|---|
| **Spraymotion System Controller Dimensions:** | 20” h x 18” w x 8” d<br>508mm h x 457mm w x 203mm d |
| **Input Power:** | 120 VAC |
| **Power Consumption:** | 240 Watt |
| **Control:** | 3 relay contact closures, one for each zone, built in timer and/or control by outside system |
| **Number of Zones:** | 3 zones |
| **Number of Spray Ports** | 25 total spray ports maximum |
| **Water Supply Pressure Range:** | 40 - 80 psi |
| **Macro Spray Port Angle:** | 60° @ 40 psi |
| **Macro Spray Port Coverage:** | Approximate 5' diameter (standard nozzle) |
| **Macro Spray Port Flow Rate:** | .57 gpm /2.16 lpm @ 40 psi |

sensoryco.

31145 Plantation Drive
Thousand Palms, California 92276
+1 760-385-3939
www.sensoryco.com

| Parameter | Value |
| --- | --- |
| **Macro Spray Port Inlet Connection:** | 1/4” |
| **Warranty:** | 1 Year, Unlimited Customer Support |